

转盘机型

立式四柱直压锁模，立式注射，中文/英文电控，荧屏显示，双比例式压力，流量油路控制，转盘，底座采用球墨铸铁一体化制造，机械结构强，压力高，速度快。

Vertical compression mold-locked, vertical injection, Chinese/English controller, screen display, double proportional pressure, oil flow control, round set. Base plate formed by nodular cast iron once. Strong mechanical structure, high pressure and fast speed.

转盘在同一水平做180°或360°交替旋转，可让操作者在固定操作面取，放成品，嵌件，操作安全性高，且可提高生产效率50%。

Rotary table rotates alternatively with an angle of 180° or 360°. It is convenient for workers to pick and put objects, high safety, increase more than 50% efficiency.

转盘扭力大小，速度快慢，减速距离，站数分割设定简单，一致性可靠度100%。

Simple setting of rotary torque size, speed, slow-down distance. 100% match consensus.

配合爱科AKMP系统，转盘运作更加迅速，平稳。

Cooperate with AKPLAS AKMP system, rotary table running more quickly and smoothly.

标准转盘分为2站或者3站，有特殊要求可选4站或更多，以达到更方便的操作及自动化连线规划，增加产能。

Standard rotary table is divided into 2 or 3 positions, also can be divided into 4 or more for special demand, to convenience operating and automatic connect planning, increase production.

电器与气压共同控制安全保护闸，在开模状态下增加阻止动模坠落的保护功能，大大增加了人身，模具的安全性。

Electric and pressure co-control the safety protection brake, in the state of open-molded, it enhances the protection function of preventing the falling of movable mold, and greatly ensures the people and mold's safety.

油路，水路，管路一体化设计，让客户接油，接水更方便，快捷。

Oil, water, and pipe circuit integration design, convenient for customers to put in oil and water.

多样化油路系统设计（半闭，全闭，伺服或高速注塑）可配合客户需求，可扩充式程序设计，与自动埋入，取出设备连线，达到全自动操作。

Diversity oil system design (semi-closed, closed, servo or high speed injection) to meet customers demands. Expandable programming, connect with automatic putting and picking devices, totally automatic.



AT-3500.2RL
锁模力 350T
Clamping Force
射出量 800-1500g
Shot Weight

AT-400.2R
锁模力 40T
Clamping Force
射出量 86-109g
Shot Weight



AT-550.2RH
锁模力 55T
Clamping Force
射出量 86-109g
Shot Weight



AT-550.2R
锁模力 55T
Clamping Force
射出量 86-109g
Shot Weight



AT-850.2RA
锁模力 85T
Clamping Force
射出量 150-250g
Shot Weight



转盘机型

AT-850.2R
 锁模力 85T
 Clamping Force
 射出量 150-250g
 Shot Weight



AT-850.3R
 锁模力 85T
 Clamping Force
 射出量 150-250g
 Shot Weight



AT-1500.2R
 锁模力 150T
 Clamping Force
 射出量 400-550g
 Shot Weight



AT-1500.3R
 锁模力 150T
 Clamping Force
 射出量 400-550g
 Shot Weight



AT-1500.2RL
 锁模力 150T
 Clamping Force
 射出量 400-550g
 Shot Weight



AT-2100.2R
 锁模力 210T
 Clamping Force
 射出量 450-800g
 Shot Weight



AT-1200.2RL
 锁模力 120T
 Clamping Force
 射出量 150-350g
 Shot Weight



转盘机型

AT-2500.2R
锁模力 250T
Clamping Force
射出量 450-800g
Shot Weight



AT-2500.2RL
锁模力 250T
Clamping Force
射出量 450-800g
Shot Weight



AT-4500.2R
锁模力 450T
Clamping Force
射出量 800-1500g
Shot Weight



AT-3500.2R
锁模力 350T
Clamping Force
射出量 800-1500g
Shot Weight



AT-4500.2RL
锁模力 450T
Clamping Force
射出量 800-1500g
Shot Weight

