

AC 系列

立式直压锁模，横式注射，无立柱，三面开放，中文 / 英文电控，荧屏显示，双比例式压力、流量油路控制，机械结构强，压力高，速度快。

Vertical compression locked-mold, horizontal injection, without vertical column, three sides opened, Chinese/English controller, screen display, double proportional pressure, oil flow control, strong mechanical structure, high pressure and fast speed.

C 型钢构，一体成型，高压弯矩变形量小，直压式锁模，双缸射出系统，精度佳，寿命长，无机柱阻隔，更便于嵌入及取出，更能配合自动化的连线作业。

C type steel structure, integration forming, small deformation under high pressure, vertical compression, dual-cylinder injection system, high precision, long using life, astylar barrier, convenient to put and pick objects, suitable for automatic operation.

射座高度整体水平升、降调整（有手动、自动两种方式），易于模具中心水准校正，让模具安装、调试更方便，杜绝跑料。

The height of injection base lift adjustment (manual and auto two types), convenient to correct of the central standards, convenient to install mold and adjust, prevent from leaking material.

多样化油路系统设计（半闭、全闭、伺服或高速注塑）可配合客户需求。

Diversity oil system design (semi-closed, closed, servo or high speed injection) to meet customers demands.

可根据客户产品需求选择标准机型、滑板机型（单模滑板、双模滑板）、转盘机型（2站式、3站式或多站式）等多种机型。

According to the customers products demands to choose standard type, sliding type (single mold sliding plate or double mold sliding plate), rotary type (2 position 3 position or more) and etc.



AC-2R(3R) Series

锁模力 45-250T
Clamping Force
射出量 30-1500g
Shot Weight



AC-750DS

锁模力 75T
Clamping Force
射出量 250g
Shot Weight



AC- Series

锁模力 45-150T
Clamping Force
射出量 30-1500g
Shot Weight



AC- DS Series

锁模力 45-150T
Clamping Force
射出量 30-1500g
Shot Weight